



millersoils.co.uk

PRODUCT DATA SHEET

INDUSTRIAL



PRODUCT NAME/VISCOSITIES:

MILLWAY RANGE

DESCRIPTION:

The Millway range is a blend of selected base stocks, a four fold additive package, with the inclusion of a tacky adhesive additive. Making it suitable for both horizontal or vertical slides and ways

APPLICATION:

Use as received for the lubrication of slideways where smooth, stick-slip-free performance is required or where a tacky adhesive lubricant is required.

USER BENEFITS:

- High lubricity prevents stick-slip of slideways.
- Outstanding anti wear and anti corrosion properties.
- Non drip formula highly suitable for the lubrication of vertical surfaces.
- Careful selection of viscosity means hydraulic performance can be achieved.

TYPICAL CHARACTERISTICS:

Millway	32	46	68	100	150	220
Specific Gravity @ 15°C	0.875	0.880	0.881	0.885	0.899	0.903
Kinematic Viscosity @ 100°C	5.7cSt	4.2cSt	8.9cSt	11.4cSt	16.8cSt	19cSt
Kinematic Viscosity @ 40°C	32cSt	46cSt	68cSt	100cSt	150cSt	220cSt
Viscosity Index	116	117	104	108	106	104
Pour Point (°C)	-15	-15	-15	-15	-15	-6
Flash Point (°C)	194	200	200	200	200	200
Health & Safety/Product Code	5180	5310	5183	5210	5186	5301

HEALTH AND SAFETY:

Health and Safety Data Sheet numbers above relate to the products listed. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

